

NovaTherm Multi-Zone Pump Pack with thermostatic mixing valve



Product Information

The ESBE compact T4 thermostatic 4 port pump set, comes complete with:

- 20°C - 55°C temperature range suited for force screed drying in accordance with (BS1264)
- 'A' rated Grundfos UPM3 Auto pump
- Integrated check valves for easy filling
- Temperature gauge
- Assembled in the UK: pre-tested, packaged and ready for instant installation
- 2 Year warranty
- Fully reversible (Left or Right sided manifold) • Side or bottom entry connections
- Available in 200mm, 210mm and 225mm manifold connection centers

Optional extras

Primary isolation valves
Safety temperature switch
Manifold isolation valves
Compression fittings



Specification

Kv: 3.4Kv (Up to 220sqm / 18kW)
Temperature range: 20°C - 55°C
Max temperature range:
Continuously = 95°C / Temporarily = 100°C
Maximum supply pressure: 10 Bar

Item	Description	Qt
1	Grundfos UPM3 Auto Pump	1
2	ESBE Thermostatic Mixing Valve	1
3	Flow / Return Elbow	1
4	2mm Rubber Washer	2
5	1 1/2" Rapid Connection Nut	2
6	Elbow Flanged	1
7	3/4" Female BSP Flow and Return	2
8	3/8" Pocket	1
9	Temperature Gauge	1
R	Return from manifold / flow to heat source	NA
H	Flow from heat source	NA

